



ENERGY TWIN-FLEX H-A

FALL ARREST LANYARD 1302-TFA

- ANSI certified hooks and carabiner
- Approved for 100 kg
- Elastic webbing

Energy Twin-Flex S is a double fall arrest lanyard with flexible webbing and ANSI certified hooks and carabiner.

SEGMENTS

- ✓ General industry
- Tower climber
- Wind energy

ARTICLES

012203166	Cresto, Energy Twin-Flex H-A, 1.9m
012203167	Cresto, Energy Twin-Flex H-A, 1.9m, cover

OVERVIEW

A double fall arrest lanyard is designed to suit you who need to move when you work at heights. With double hooks you always have a hook anchored when you move with the other hook. This is to provide the optimum security during work at, for example, pylons, wind turbines or industries.

Energy Twin-Flex Cover+ is designed with a flexible tube with internal elasticity, which allows you to stretch the line to a maximum length of 1.9 meters. At the beginning of the lanyard there is an external absorber mounted which is released in case of a fall and catches you. The cover on the absorber can easily be replaced if it becomes dirty or damaged to ensure that the rope underneath is protected in the best way.

Energy Twin-Flex S has ANSI certified hooks and carabiner and can withstand a user weight of up to 100 kg. The fall arrest lanyard can also be purchased with a protection cover.

CRESTO GROUP

Diabasgatan 16 254 68 Helsingborg Sverige T. +46 42 563 00 E. support@crestogroup.com www.crestogroup.com



SPECIFICATION

PRODUCT PROPERTIES

Attaching connector 1	ANSI certified triple lock carabiner in aluminum
Attaching connector 2	Big ANSI certified aluminum hook with 64 mm opening
Energy absorber	Yes
Fall indicator	Yes
Mechanics	Tear-webbing absorber
Maximum number of users	1
Maximum load (kg)	100.0
Minimum working temperature (c)	-40.0
Maximum working temperature (c)	100.0
Minimum breaking strength - MBS (kN)	15.0
Material	Polyamide

CLASSIFICATION

PPE-category	Category 3
EN-standard	EN 355 : 2002
Notified body	0402, RISE Research Institutes of Sweden, Box 857, SE-50115 Borås, Sweden

ANNUAL INSPECTION

Annual inspection	Yes, every 12 months
Life span	10 + 2 years. Product lifecycle 10 years + 2 years stock keeping
Warranty	2+1 year when registered in Inspector
Identification	Serial number
RFID	Yes

DOCUMENTS

Declaration of Conformity	Yes
Manual languages	Danish (DA), English (EN), Finnish (FI), French (FR), German (DE), Greek (EL), Norwegian (NO), Spanish (ES), Swedish (SV)

CRESTO GROUP

Diabasgatan 16 254 68 Helsingborg Sverige T. +46 42 563 00 E. support@crestogroup.com www.crestogroup.com



IMAGES



CRESTO GROUP

Diabasgatan 16 254 68 Helsingborg Sverige T. +46 42 563 00 E. support@crestogroup.com www.crestogroup.com

