

VENTURE II® READERS

Strategically Placed Lens Inserts



Black Frame

Part	Mag Strength	Lens
ESB1810R10●●●	+1.0	<input type="checkbox"/> Clear
ESB1810R15●●●	+1.5	<input type="checkbox"/> Clear
ESB1810R20●●●	+2.0	<input type="checkbox"/> Clear
ESB1810R25●●●	+2.5	<input type="checkbox"/> Clear
ESB1810R30●●●	+3.0	<input type="checkbox"/> Clear






- Temples adjust to four different lengths.
- 9.75 base curved lens provides full side protection.
- Strategic placement of lens insert is out of user's direct line of vision.
- Nose buds secure the glass and prevent slipping while providing a pillow soft fit.

GENERAL SPECIFICATION
Bridge: 10.5mm
Lens Base: 9.75 Curve
Lens Size Diagonal: 56mm
Lens Size Vertical: 45mm
Lens Thickness: 2.2mm
Overall Length (Lens-Tip): 150-163mm
Overall Width (Hinge-Hinge): 142mm
PD: 68mm
Weight: 27gm
Closest point between lens: 7mm
Closest point between temple tips: 95-98mm

VENTURE II[®] READERS

PACKAGING
Polybag: 1pc
Inner Box: 6 pcs
Outer Carton: 150 pcs

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	Full eye protection
Frame	Polycarbonate	Lens clip in frame
Side Shield	Polycarbonate	Integral to lens
Nose Piece	Bridge - Polycarbonate	Integral to lens
	Nose Pad - PVC	Snap in nose piece
Sleeve	Nylon	4 length position adjust
Temple	Nylon	Length adjustable
Hinge	Polycarbonate/Nylon	3 barrel type
Screw	Stainless steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
ESB1810R10	 Clear +1.0	2C - 1.2 P 1 F CE	CE P EN166 F
ESB1810R15	 Clear +1.5	2C - 1.2 P 1 F CE	CE P EN166 F
ESB1810R20	 Clear +2.0	2C - 1.2 P 1 F CE	CE P EN166 F
ESB1810R25	 Clear +2.5	2C - 1.2 P 1 F CE	CE P EN166 F
ESB1810R30	 Clear +3.0	2C - 1.2 P 1 F CE	CE P EN166 F

LENS MARKING

Code (field of use):

2 or 3: UV Filter
5 or 6: Solar Filter

Color Perception:

C: Unimpaired color perception

Protection Class:

1.2 to 6: Degree of visible light filtration

Optical Class:

1: High optical quality / No optical distortion

Mechanical Strength:

S: Extra strong, resists a 22mm, 43g ball falling 1.30 m/s
F: Low energy impact, resists a 6mm, 0.86g at 45 m/s
B: Medium energy impact, resists a 6mm, 0.86g at 120 m/s
A: High energy impact, resists a 6mm, 0.86g at 190 m/s

Symbols:

P: Manufacture Indication
N: Filter with Anti-Fog features
CE: European Standard

FRAME MARKING

Symbols:

CE: European Standard
P: Manufacture Indication
EN166: CE specification for protective eyewear

Mechanical Strength:

F: Low energy impact
B: Medium energy impact
BT: Medium energy impact at extreme temperatures

Protection Class:

3: Protection against liquid droplets
4: Protection against large dust