



jalas® EXALTER 9995

ASTM F2413-18 M/I/C/SD 35/PR    EN ISO 20345:2022 S3S, HR0, FO, SC



[Learn more](#)

NEW SUSTAINABLE GENERATION

Exalter’s new generation is upgraded with several recycled and bio-based materials without compromising the superior combination of durability, comfort, and lightness that users have relied on for years. Bio-based microfiber water repellent upper keeps the feet dry. BOA® Fit System (from recycled material) on the side eliminates pressure points. Aluminum toe cap and recycled metal-free nail protection insert with high-grip Vibram® recycled nitrile rubber outsole.

CHARACTERISTICS	FUNCTIONS	
<ul style="list-style-type: none"><li>• High level of protection</li><li>• Excellent grip</li><li>• Perfect fit</li><li>• Extra comfortable</li><li>• Excellent shock absorption</li></ul>	<ul style="list-style-type: none"><li>• Heat-resistant outsole</li><li>• Oil-resistant outsole</li><li>• Anti-static properties</li><li>• Polstered shaft edge</li><li>• Ventilating insole</li><li>• BOA® Fit System</li><li>• Quick-tie</li><li>• Stabilizator</li><li>• Water repellent</li><li>• Ergonomically shaped</li><li>• Soft</li><li>• Specially designed details</li><li>• Double shock absorption zones</li></ul>	<ul style="list-style-type: none"><li>• Conforms with IEC 61340-5-1 (ESD)</li><li>• Free from animal-derived materials</li></ul>





PREVENTS RISK OF

Toe injuries, Nail penetration, Sprain injuries, Antistatic

PRIMARY ENVIRONMENTS OF USE

Outdoors, Indoors, All-year use, Warm surfaces, Environments with risk for outsole penetration, Dry environments, Clean environments, Moist environments, Dirty environments

PRIMARY AREAS OF USE

Agricultural work, Assembly, Building and construction, Carpentry, Concrete work, Construction, Engineering, Fine assembly, Fishing industry work, Forest work, Gardening, Inspection work, Installation work, Machine driving, Machine operating, Metalwork, Paper industry work, Repair work, Sheet-metal work, Transport work, Warehouse work, Wood industry work

SPECIFICATION

TYPE Safety footwear, Low shoes

CATEGORY Cat. II

NAIL PROTECTION MATERIAL EcoFlex Zero perforation textile

FITTING Regular

COLLECTION Exalter

UPPER MATERIAL Microfiber

TOECAP MATERIAL Aluminium

LINING MATERIAL Polyester

INSOLE JALAS 8304 FX3 Soft

MIDSOLE MATERIAL PU midsole

OUTSOLE MATERIAL Nitrile rubber outsole

FASTENING BOA® Fit System

COLOUR Black

NET WEIGHT, (SIZE 42) 1.23 kg

COMPLIANCE



ASTM F2413-18  
M/I/C/SD 35/PR



EN ISO 20345:2022  
S3S, HR0, F0, SC

TP TC 019:2011

FEATURES



Aluminium toecap



Nail protection in  
plasma-treated  
composite (PTC)  
textile



Heat-resistant outsole



Water repellent



Oil-resistant outsole



Ergothon Shock  
Absorption System



Stabilizator



Anti-static properties



ESD

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
34	1,5	2,5	3,5	9995-34	6408487554599
35	2	3.5	4	9995-35	6408487554643
36	3	4	5	9995-36	6408487554698
37	4	5	6	9995-37	6408487554742
38	5	5.5	6.5	9995-38	6408487554797
39	6	6.5	7.5	9995-39	6408487554841
40	6.5	7.5	8.5	9995-40	6408487554896
41	7	8	9	9995-41	6408487554940
42	8	9	10	9995-42	6408487554995
43	9	9.5	11	9995-43	6408487555046
44	10	10.5	11.5	9995-44	6408487555091
45	10.5	11	12.5	9995-45	6408487555145
46	11	12	13	9995-46	6408487555190
47	12	13	14	9995-47	6408487555244

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden  
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com