



 TEMPUS 5668

ASTM F2413-18 M/I/C/SD 35/PR ASTM F3445-21 SR EN ISO 20345:2011 S1, P, SRC



COMFORTABLE SAFETY SHOE WITH BOA FIT SYSTEM

Ventilated, sporty, and comfortable safety shoe with green details and advanced shock absorption with PORON XRD, BOA® Fit System, protective toe cap and flexible nail penetration insert made of textile material. The well proven outsole has a very effective grip pattern and is made of a special nitrile rubber for high durability.

CHARACTERISTICS	FUNCTIONS
• Excellent grip • Perfect fit • Extra comfortable • Very breathable • Excellent shock absorption • Extremely light	• Low weight • Oil-resistant outsole • Anti-static properties • Ventilating insole • BOA® Fit System • ESD • Ergonomically shaped • Soft • Double shock absorption zones • Conforms with IEC 61340-5-1 (ESD) • Breathable



PREVENTS RISK OF

Toe injuries, Nail penetration, Antistatic, Slipping

PRIMARY ENVIRONMENTS OF USE

Indoors, Environments with risk for outsole penetration, Dry environments, Clean environments

SPECIFICATION

TYPE Safety footwear, Low shoes

CATEGORY Cat. II

NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile

FITTING Narrow/Regular

COLLECTION Tempus

UPPER MATERIAL Microfiber, PU-coated leather, Textile

TOECAP MATERIAL Steel

LINING MATERIAL Polyester, polyamide

INSOLE JALAS 8104 FX2 Pro Slim

INNERSOLE MATERIAL Textile, Soft EVA, Polyester-based conductive thread, Double shock absorption zones in PORON® XRD®

MIDSOLE MATERIAL EVA

OUTSOLE MATERIAL Nitrile rubber outsole

FASTENING BOA® Fit System

COLOUR Black

NET WEIGHT, (SIZE 42) 0.96 kg

COMPLIANCE



TP TC 019:2011

EN ISO 20345:2011
S1, P, SRC



ASTM F2413-18
M/I/C/SD 35/PR



ASTM F3445-21
SR



FEATURES



Steel toe cap



Nail protection in
plasma-treated
composite (PTC)
textile



Oil-resistant outsole



Anti-static properties



ESD

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
35	2	3.5	4	5668-35	6408487542732
36	3	4	5	5668-36	6408487542787
37	4	5	6	5668-37	6408487542831
38	5	5.5	6.5	5668-38	6408487542886
39	6	6.5	7.5	5668-39	6408487542930
40	6.5	7.5	8.5	5668-40	6408487542985
41	7	8	9	5668-41	6408487543036
42	8	9	10	5668-42	6408487543081
43	9	9.5	11	5668-43	6408487543135
44	10	10.5	11.5	5668-44	6408487543180
45	10.5	11	12.5	5668-45	6408487543234
46	11	12	13	5668-46	6408487543289
47	12	13	14	5668-47	6408487543333
48	13	13.5	14.5	5668-48	6408487543388

ejendals

Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com